

FRAMELESS TRAILER

Model: FC2SD40



BODY Aluminum Smooth Side Polished		SUBFRAME	
Body Length	40	Model	Tandem
Body Width	102 Wide	Subframe Width	47 1/2
Side Height	72 Total 70	Suspension Spacing	10' 2" 5th Wheel HT 49" std
Side Thickness	3/16 Sheet Ht 72	Pin to Axle	439 in. Aluminum Air Tanks
Top Rail	HD 9" Top Rail	Springs	Air 5 HXL Grease Hubs
Top Rail Option	Radius Flush w/ Bulkhead & Rear Pocket	Suspension	Intraax AAT 250 Galv / Soft coat
Bulkhead Height	76.5 in 2.75 in Taper	Suspension Setting	2" Ahead
Tow Motor Package	No	Tire Size	24.5
Coil Rack	No	Axles	77.5 Trk 5/8 Wall 16.5" X 7" Shoe TP
Floor	1/4" with Last 10' 3/8"	Wheels	24.5 10 Hole Hub Piloted
Liner	None	Wheel Type per axle	4 Alcoa LVL 1 Buffed 8.25 Wheels
Crossmembers	12" Apart	Hub & Drum	Cent w/ ADI HP 10ST HXL5 Grease
Rear Pocket	Extruded	Tire Type	Yokohama 108R 11R 24.5 16 ply
Apron	4" x 1/2"	ABS System	2S1M on Rear
Apron Style	Weld On	Brakes	16 1/2" X 7"
Mid Turn Signal	1 Pair LED Combo Marker/ Turn In Bottom Rail	Dust Shields	No
Light Panel	LED, 3 Large - 3 Small - 3 Large	Tire Carrier	No
'X' = Backup Light	OOO ooo OOO	Mud Flaps	Standard & Full across Rear
Marker Lights	LED (Lifetime Harness)	Tow Hook	2 Bolt On
Number	11 In Bottom Rail	DRAFT ARM	
Backup Lights	All (6) Integrated Back Up 44556R	Hoist	Custom 8-5-285
Tarp	None	Pin Setting	16
Roll Cap	No	Landing Gear	Jost Alumilight AX150 2 Speed DS
Tarp Bows	No	Gladhands	Serv-Emer
Bulkhead Mandoor	Driver Side w/ Step & Handle	Hydraulic Hose Fitting	Wingnut w/ 108" Hose
Tarp Bar	No	Ball Valves	Gate-Dump-Lift
Tarp Hooks	No	Additional Controls	Yes - See Notes
Ladders	Rear Panel In & Out Dr Sd	Draft Arm Type	Aluminum
Shovel Hanger	Yes - Indise On Doghouse Side	Draft Arm Length	224"
Body Fenders	Square Off Front	Support Plate	Extruded
Panel	74	LIFT AXLE(S) 1	
Panel Finish	Polished	Suspension	Intraax AAT-250 Gal / Soft Coat
TAILGATE Smoothside ANGLE ON TOP		Axles	77.5 Trk 5/8 Wall 16.5" X 7" Shoe TP
Height	73 1/2	Tires	Yokohama 108R 11R 24.5 16 ply
Winders	1 Each Side 2 Bottom Stainless Steel	Wheels	24.5 10 Hole Hub Piloted
Water Seal	Yes	Wheel Type per axle	4 Alcoa LVL 1 Buffed 8.25 Wheels
Spreader Chains	No	Hub & Drum	Cent w/ ADI HP 10ST HXL5 Grease
Hinge Type	Overslung w/ Ground Control Swing To D/S	Brakes	7" w/30-30 Chambers
3/8" Strap	Bottom	Distance	10' 2"
Coal Door	14" Alum Handle w/ Gravity Lock & Cover	Lift Tire Size	24.5
Coal Chute	4"	Bulkhead Flags	Yes
Vertical Bracing	No	Paint	Black
Remote Greaser	STD Gate Linkage	Pin Stripe	No

1) Aux 7 way (ISO) for all controls; back up lights (black), lift axle w/ brake release (yellow), suspension (green), tailgate (red)

2) Ball Valve Controls and Air Gauge For Bag Pressure in Composite Box Between Axles.

1) Aluminum mud flaps - 36" aluminum +10" rubber, center panel and cap off - 3 locations - front & rear of front axle, front of rear axle